

# Emergency Lighting LED Satellite Weatherproof



CAT NO. **684875** and **684879**



- Non-maintained operation
- Computerised (Axiom/Commander) and non-computerised (SPU) versions
- Less than 1W in stand-by mode (SPU)
- Weatherproof IP55
- Robust design
- One high brightness LED
- Very long lamp life
- D25/D25 classification
- AS2293 compliant

Product specifications		
Cat No	684875	684879
Type	SPU	Axiom/Commander*
Operation mode	Non-maintained	
Light source	1x2W HBLED	
Battery	NiCd 5x1 Sub-C-cells linear - 6.0V d.c. 1.5Ah	
Charging mechanism	Dual rate charge	
Charging current	150mA (hrc) - 40mA (lrc)	
Operating voltage	240V a.c. +/- 6% 50Hz	
Power consumption	0.95W	1.4W
Box constructions	Polypropylene box	
Cover	Transparent polycarbonate	
Operating temperature	0°C to + 40°C	
Lighting classification	C <sub>0</sub> /C <sub>90</sub> D25/D25	
IP rating	IP55	
Replacement battery	Cat No 682353	

\* When using the item Cat No 684879 on a Commander network, a communications cable Cat No 201058 must be ordered separately

Packaging specifications		
Type	SPU	Axiom/Commander
Single box quantity	1	1
Single box dimensions (WxHxD)	290mm x 190mm x 97mm	290mm x 190mm x 97mm
Single box weight	1.30kg	1.35kg

Premium SPU			
684875	Satellite LED 1x02W Weatherproof Surface Mount	SRLED102WP	9322276848751
Axiom SPU			
684879	Axiom Satellite LED 1x02W Weatherproof Surface Mount	AXSRLED102WP	9322276848799

Specifications subject to change without prior notice.

# Emergency Lighting LED Satellite Weatherproof

CAT NO. **684875 and 684879**

HPM Legrand - AUS  
1300 369 777  
www.hpm.com.au

HPM Legrand - NZ  
0800 476 009  
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or  
HPM Legrand Sales Office for pricing.